

















# 5/2-directional valve, Series 581, size 1

- ISO 5599-1
- ISO 1
- 5/2
- with air spring return
- $Q_n = 1400$  l/min
- Compressed air connection output Base plate ISO 5599-1
- Electrical connection Plug, EN 175301-803, form A
- Manual override without detent



Version	Spool valve
Sealing principle	Soft sealing
Blocking principle	Single base plate principle
Connection type	Plate connection
Standards	ISO 5599-1, ISO 1
Working pressure min./max.	See table below
Control pressure min./max.	1,3 ... 16 bar
Ambient temperature min./max.	-15 ... 50 °C
Medium temperature min./max.	-15 ... 50 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 5 mg/m <sup>3</sup>
Nominal flow $Q_n$	1400 l/min
Flow conductance C	5,2 l/(s*bar)
Protection class with connection	IP65
Duty cycle	100 %
Typ. switch-on time	15 ms
Typ. switch-off time	28 ms
Mounting screw	with hexagon socket
Mounting screw tightening torque	2 Nm
Weight	0,38 kg

## Technical data

Part No.		MO	Operationalvoltage DC	Operationalvoltage AC 50 Hz	Voltage tolerance DC
5811670540			24 V	42 V	-10% / +10%
5811670440			-	230 V	-
5811671540			24 V	42 V	-10% / +10%
5811671440			-	230 V	-
5811672540			24 V	42 V	-10% / +10%
5811672440			-	230 V	-
5811673540			24 V	42 V	-10% / +10%
5811673440			-	230 V	-

Part No.	Voltage tolerance AC 50 Hz	Power consumption DC	Holding power AC 50 Hz	Switch-on power AC 50 Hz
5811670540	-10% / +10%	6,7 W	7,7 VA	12 VA

Part No.	Voltage tolerance AC 50 Hz	Power consumption DC	Holding power AC 50 Hz	Switch-on power AC 50 Hz
5811670440	-10% / +10%	-	10,8 VA	15,2 VA
5811671540	-10% / +10%	6,7 W	7,7 VA	12 VA
5811671440	-10% / +10%	-	10,8 VA	15,2 VA
5811672540	-10% / +10%	6,7 W	7,7 VA	12 VA
5811672440	-10% / +10%	-	10,8 VA	15,2 VA
5811673540	-10% / +10%	6,7 W	7,7 VA	12 VA
5811673440	-10% / +10%	-	10,8 VA	15,2 VA

Part No.	Pilot	Working pressure min./max.	Electrical connection Pilot valve	Throttle
5811670540	internal	1,3 ... 16 bar	Plug EN 175301-803, form A	-
5811670440	internal	1,3 ... 16 bar	Plug EN 175301-803, form A	-
5811671540	internal	1,3 ... 16 bar	Plug EN 175301-803, form A	with throttle
5811671440	internal	1,3 ... 16 bar	Plug EN 175301-803, form A	with throttle
5811672540	external	-0,95 ... 16 bar	Plug EN 175301-803, form A	-
5811672440	external	-0,95 ... 16 bar	Plug EN 175301-803, form A	-
5811673540	external	-0,95 ... 16 bar	Plug EN 175301-803, form A	with throttle
5811673440	external	-0,95 ... 16 bar	Plug EN 175301-803, form A	with throttle

Differential piston, signal 14 has priority, The minimum pilot pressure at port 14 is dependent on the pressure in port 1., Nominal flow Qn at 6 bar and  $\Delta p = 1$  bar, MO = Manual override

## Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

## Technical information

Housing	Aluminum
Seals	Acrylonitrile butadiene rubber

# Dimensions

## Dimensions

